



## Tagalong 6 Ton Series

• G.V.W.R. - 12,000 #	• Axles - 2 Dexter 6,000 # single wheel electric brake axles
• G.A.W.R. (Each Axle) -6,000 #	• Suspension - Multi-leaf slipper spring w-equalizer
• Coupler - 3 position adjustable	• Tires - 750-16"- 10 Ply load range E
• Safety Chain - 3/8 grade 43 with hooks	• Wheel - 6.75 x 16" 8 bolt white spoke
• Jack - 10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame - 12 @ 16 # I-beam	• Lights - D.O.T. Stop, tail, turn, and clearance
• Crossmembers - 3" channel on 16" center	• Elec. Plug - 7-way RV
• Side rails - 6" channel with stake pockets on 24" center with rub rails	• Paint - High solids acrylic enamel

### Standard Features

### Optional Features

• Crossmembers on 16" centers	• Dual jacks
• Sealed modular wiring harness	• Steel deck
• Electric breakaway	• Vacuum over hydraulic
• E-Z Lube axles	• Electric over hydraulic
• 5' Dovetail	• 14,000 G.V.W.
• 5' Ramps	• Popup dovetail
• Tool tray in tongue	• D-Rings

### Dimensions

Length	A	B	C	D	E
25'	300"	178.75"	68"	37"	96"
29'	348"	202.75"	68"	37"	96"

