



Commercial Series

10TC Tagalong tilt Series

| | |
|--|--|
| <ul style="list-style-type: none"> • G.V.W.R. - 20,000 # • G.A.W.R.(Each Axle) - 10,000# • Coupler - 3 position pintle ring • Safety Chain -3/8 grade 43 with hooks • Jack-10,000 # drop leg • Frame -12 @ 19# I-beam • Crossmembers - 4" channel on 16" center • Side rails - 8"channel with 10 D-Rings | <ul style="list-style-type: none"> • Axles - 2 Dexter 10,000 # dual wheel electric brake axles • Suspension - Multi-leaf slipper spring • Tires - 235-80R-16" load range D • Wheel - 6.75 x 16" dual 8 bolt • Deck - 2" oak • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug 7-way RV • Paint - High solids acrylic enamel |
|--|--|

Standard Features

Optional Features

| | |
|--|---|
| <ul style="list-style-type: none"> • 16" dual wheels • Crossmembers on 16" centers • Sealed modular wiring harness • Electric breakaway • Oil bath axle • Tool box with lid in tongue • Rubber mounted lights | <ul style="list-style-type: none"> • Dual jacks • Air brakes • 12 Ton capacity • Vacuum over hydraulic • Electric over hydraulic • Stake pockets & Rubrails • Spare tire mt. |
|--|---|

Dimensions

| Length | A | B | C | D | E |
|--------|------|--------|-----|-------|-----|
| 25' | 288" | 150.5" | 68" | 38.5" | 96" |
| 29' | 336" | 174.5" | 68" | 38.5" | 96" |

