

6 T Equipment Series

<ul style="list-style-type: none"> • G.V.W.R.-12,000 # • G.A.W.R.(Each Axle) - 6,000 # • Coupler - 2 - 5/16" adjustable • Safety Chain - 3/8 grade 43 with hooks • Jack -7,000 # drop leg • Frame - 6" channel • Crossmembers - 3" channel • Fenders - 10"x72" diamond plate with backs • Tongue - 6" channel wrap around • Bed width - 81" 	<ul style="list-style-type: none"> • Axles - 2-6,000 # cambered brake axles • Suspension - Slipper spring with equalizer • Tires - LT 750- 16"load range E • Wheel -16" 8 bolt white spoke • Deck - 2" pressure treated pine • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel • Ramps - 4' fold down • Sealed modular wiring harness
---	--

Standard Features

Optional Features

<ul style="list-style-type: none"> • 16" white spoke • Pressure treated decking • Light protectors • Electric breakaway • E-Z Lube axles 	<ul style="list-style-type: none"> • Side rails • Steel deck • 48" split gate • Self Cleaning Dovetail • D-Rings
---	---

Dimensions

Length	A	B	C	D	E
16'	192"	113"	43.5"	26"	81"
18'	216"	125"	43.5"	26"	81"
20'	240"	137"	43.5"	26"	81"
22'	264"	149"	43.5"	26"	81"

