



Gooseneck 10 Ton Series

• G.V.W.R. - 20,000 #	• Axles - 2 Dexter 10,000# dual wheel electric brake axles
• G.A.W.R.(Each Axle) - 10,000 #	• Suspension - Multi-leaf slipper spring with equalizer
• Coupler - 2-5/16" adjustable	• Tires - 7:50 x 16" load range E
• Safety Chain-3/8 grade 43 withhooks	• Wheel - 6.75 x 16" dual 8 bolt
• Jack - 10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame - 12 @ 19 I-beam	• Lights - D.O.T. Stop, tail, turn, and clearance
• Crossmembers -3" channel on 16" center	• Elec. Plug - 7-way RV
• Side rails - 6" channel with stake pockets on 24"center with rub rails	• Paint - High solids acrylic enamel

Standard Features

Optional Features

• 16" dual wheels	• Dual jacks
• Crossmembers on 16" centers	• Steel deck
• Sealed modular wiring harness	• Deck over neck
• Electric breakaway	• 12 Ton capacity
• Oil bath Axles	• Vacuum over hydraulic
• 5' Dovetail	• Electric over hydraulic
• 5' Ramps	• Headache rack
• Rubber mt. lights	• D-Rings
• Spare tire mt.	• Spring-loaded Ramps

Dimensions

Length	A	B	C	D	E
21'	252"	150"	91"	37"	96"
25'	300"	175"	91"	37"	96"
29'	348"	209"	91"	37"	96"
31'	372"	224"	91"	37"	96"
33'	396"	242"	91"	37"	96"
35'	420"	266"	91"	37"	96"
40'	480"	336"	91"	37"	96"

